


160 W continuous program power capacity
 1.4" horn throat diameter
 75 mm (3 in) aluminium voice coil
 Titanium diaphragm
 500 - 18000 Hz response
 107 dB sensitivity
 Shorting copper cap for extended HF response



SPECIFICATIONS

Driver mounted on B&C ME 90 horn.

Throat Diameter	36 mm (1.4 in)
Nominal Impedance	8 Ω
Minimum Impedance	8 Ω
Nominal Power Handling	80 W 2 hour test made with continuous pink noise signal within the range from the recommended crossover frequency to 20 kHz. Power calculated on rated minimum impedance.
Continuous Power Handling	160 W Power on Continuous Program is defined as 3 dB greater than the Nominal rating.
Sensitivity	107 dB Applied RMS Voltage is set to 2.83 V for 8 ohms Nominal Impedance.
Frequency Range	0.5 kHz - 18 kHz
Recommended Crossover	1 kHz 12 dB/oct. or higher slope high-pass filter.
Voice Coil Diameter	75 mm (3 in)
Winding Material	Aluminium
Inductance	0.14 mH
Flux Density	1.8 T
Diaphragm Material	Titanium
Min Frequency Range	0.5 kHz
Max Frequency Range	18 kHz

MOUNTING AND SHIPPING INFO

Four M6 holes 90° on 102 mm (4 in) diameter

Overall Diameter	170 mm (6.69 in)
Depth	64 mm (2.52 in)
Net Weight	4.44 kg (9.79 lb)
Shipping Units	1 pcs
Shipping Weight	4.56 kg (10.05 lb)
Shipping Box	190x190x80 mm (7.48x7.48x3.15 in)

SERVICE KITS

HF replacement-diaphragm	MMD3A8
--------------------------	--------